

1 -800-283 -6266 phone: (713) 466-1449

email: customerservice@enconsafety.com

PEDESTAL MOUNT EYE/ FACEWASH WITH YELLO-BOWL®

PART NUMBER: 01035402

SP ECIFICATIO N:

party certified to ANSI Z358.1, Third eye/facewash shall deliver 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eye/Facewash shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½" chrome plated (CP) single motion activation Istay open ball valve with CP ball. Evewash shall include SS actuator with actuation graphic, 7" X 11" (17.8 cm X 27.9 cm) sign, ½" (CP) brass supply piping and schedule 80 hot dip galvanized pedestal mount/drain for free-standing installation. Unit must be supplied with self-adjusting 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eye/Facewash heads with float off covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS plastic Yello-Bowl®. Float off covers are secured with stainless steel bead chains and provided to inhibit dust and/or contamination when not in use. Eye/Facewash units that provide improper flow pattern or contain deteriorating screens/filters are not

Encon Safety Products Model 01035402 includes pedestal mount facewash with Yello-Bowl *

*Note: Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PIPING: ½" Chrome plated brass supply piping, schedule 80 hot dip galvanized pedestal. VALVES: ½" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic. HEAD: ABS plastic dual stream heads with ABS plastic float off covers secured with stainless steel bead chains. BOWL: High visibility ABS plastic Yello-Bowl®. REGULATOR: Self-adjusting 8.0 gpm (30.3 lpm) regulator assures a constant and even dual stream flow pattern under varying hydraulic conditions.

SUPPLY: ½" NPT

WASTE: 1 1/4" NPT WEIGHT: 25 lbs (11.34 kgs)



Doc. No: 01035402.3 Sec: Eye/Face washes © 2023 Encon Safety Products, Inc.



